

FG 250



⚡ 15 - 35 W
💡 1569 - 4129 lm
📌 For plasterboard ceilings and walls

FG 300




⚡ 15 - 30 W
💡 1937 - 3644 lm
📌 For Grijato ceilings

FG 595 **TOP**



⚡ 18 - 81 W
💡 2202 - 12219 lm
📌 Luminaire with uniform light distribution

FG 240



⚡ 20 - 21 W
💡 2303 - 2513 lm
📌 For slatted ceilings

FT 65 **NEW**



⚡ 10 - 20 W
💡 1048 - 1747 lm
📌 For accent lighting

FT 250



⚡ 10 W
💡 1112 lm
📌 Recessed spotlight

FG 67 **NEW**



⚡ 11 - 100 W
💡 1186 - 11787 lm
📌 High IP

FD 111



⚡ 100 - 220 W
💡 12381 - 33091 lm
📌 High IP. 5 mounting methods

FG 180



⚡ 21 - 50 W
💡 2410 - 6217 lm
📌 Universal rectangular luminaire

FG 181



⚡ 32 - 44 W
💡 4010 - 5700 lm
📌 For suspended ceilings

FS 180



⚡ 36 W
💡 3980 - 4083 lm
📌 For schools, optional modification with protective grille

FT 185



⚡ 47 - 62 W
💡 6893 - 9396 lm
📌 Different light distribution curves. Lighting of different areas

FT 81



⚡ 28 W
💡 2294 lm
📌 Recessed spotlight

FI 130



⚡ 8 - 15 W
💡 648 - 1072 lm
📌 ABS plastic luminaire with high IP

FG 190



⚡ 78 W
💡 11113 lm
📌 High IP. Tempered glass

FD 112



⚡ 100 - 200 W
💡 12681 - 32302 lm
📌 High IP. Tempered glass

FG 88




⚡ 8 - 14 W
💡 565 - 1170 lm
📌 Two sizes available for construction «designs»

FS 595



⚡ 36 - 52 W
💡 4629 - 6388 lm
📌 School luminaire

FS 500



⚡ 36 W
💡 4417 lm
📌 School luminaire with high IP

FT 91



⚡ 10 - 40 W
💡 1100 - 3800 lm
📌 For accent lighting

FT 85 **TOP**



⚡ 30 - 40 W
💡 3066 - 3904 lm
📌 Rotation of the lighting part

FI 595 **TOP**



⚡ 32 - 81 W
💡 3893 - 11962 lm
📌 For medical clean room with high IP

FG 50 EX



⚡ 20 - 100 W
💡 1399 - 8325 lm
📌 Explosion-proof luminaire

FG 120



⚡ 100 - 220 W
💡 14186 - 31612 lm
📌 High IP. Warranty - 7 years

FM 595



⚡ 32 - 44 W
💡 4019 - 5643 lm
📌 Luminaire-irradiator with UV lamps

FS 10



⚡ 20 W
💡 2442 lm
📌 To illuminate black/whiteboards

FL 58 **TOP**



⚡ 12 - 75 W
💡 1668 - 9508 lm
📌 For connection in a single line and quick installation

FG 60




⚡ 33 - 70 W
💡 4244 - 8787 lm
📌 High IP

FG 50



⚡ 20 - 112 W
💡 1975 - 11595 lm
📌 High IP. Optional modification with protective grille

FI 180



⚡ 21 - 44 W
💡 2400 - 5910 lm
📌 High IP. For different types of ceilings

FD 111 EX



⚡ 100 - 220 W
💡 11297 - 25883 lm
📌 Explosion-proof luminaire

FP 200



⚡ 20 - 30 W
💡 1582 - 2321 lm
📌 Tempered Glass Spotlight

FL 60



⚡ 34 - 72 W
💡 4157 - 7636 lm
📌 Line connection modifications

FL 60 DESIGN



⚡ 17 - 52 W
💡 2112 - 5812 lm
📌 Various types of connections for design solutions

FL 61



⚡ 34 - 72 W
💡 4157 - 7636 lm
📌 Recessed luminaire

FI 135



⚡ 32 - 49 W
💡 4553 - 6519 lm
📌 Plastic luminaire with a high IP65

FG 55 **TOP**



⚡ 11 - 100 W
💡 1614 - 15706 lm
📌 High IP. Optional modification with protective grille

FG 55 DC **NEW**



⚡ 12 - 20 W
💡 1637 - 3219 lm
📌 Extra low voltage lamp

FP 150



⚡ 50 - 150 W
💡 6282 - 21422 lm
📌 Lensed luminaire in aluminum housing

FP 80 **NEW**



⚡ 20 - 40 W
💡 3333 - 6432 lm
📌 High performance luminaire. For facades and surrounding areas

FL 81 **NEW**



⚡ 17 - 45 W
💡 2428 - 6756 lm
📌 Fast installation. Durable housing materials

FL 1500 **TOP**



⚡ 20 - 75 W
💡 2560 - 8912 lm
📌 Various types of connections

FI 350



⚡ 100 W
💡 13321 lm
📌 Recessed luminaire with tempered glass (for gas stations)

FI 600



⚡ 100 W
💡 12414 lm
📌 Lensed-recessed luminaire (for gas stations)

FG 55x2



⚡ 110 - 200 W
💡 15944 - 27648 lm
📌 High IP double luminaire

FG 100 **TOP**





⚡ 100 - 1000 W
💡 12597 - 164820 lm
📌 Modular aluminum spotlight

3D



📌 Development of a unique design. Housing material - polycarbonate

 	Streets	Industrial enterprises	Warehouses	Outdoor lighting	Other lighting	Offices	Shopping malls	Educational institutions	Spotlights	Sport facilities	Emergency lighting	Petrol stations	Clean rooms	Commercial areas	Ex lighting	Business lighting
FG 250					•	•	•									
FG 300					•	•	•									
FG 595		•				•	•					•				•
FG 180		•				•	•					•				•
FG 181		•				•	•									•
FM 595						•										
FG 88						•										
FS 595								•								
FS 500								•								
FS 180								•								
FS 10								•								
FL 58						•	•					•		•		•
FL 60						•	•					•		•		•
FL 61						•	•					•		•		•
FL 60 DESIGN						•	•					•		•		•
FL 30						•	•					•		•		•
FL 1500						•	•					•		•		•
FG 60		•				•	•									•
FG 240						•	•									•
FT 91							•							•		•
FT 65							•							•		•
FT 85							•							•		•
FT 85							•							•		•
FT 81							•							•		•
FT 250							•							•		•
FI 130		•			•		•				•					•
FI 350												•				
FI 600												•				
FI 135		•	•				•									•
FG 67		•	•				•				•	•				•
FG 50		•					•				•	•				•
FG 55		•					•					•				•
FG 55X2		•	•													
FG 55 DC		•									•					
FG 190		•	•									•				
FD 111		•	•				•		•	•						•
FD 112		•	•				•		•	•						•
FG 120		•	•						•	•						
FI 595		•											•			
FI 180		•											•			
FD 111 Ex		•										•			•	
FG 50 Ex		•										•			•	
FG 100	•			•			•				•					•
FP 200		•	•	•					•	•						
FP 150			•	•										•		
FP 80	•			•			•					•				•
FZ 100						•	•					•		•		•
FZ 101						•	•					•		•		•



SMART MAP

for LED lighting